





	CityRide Skool 16	CityRide Skool 20
Emission	Bharat Stage III	Bharat Stage III
Chassis Platform	Tata SFC 410/27 EX	Tata SFC 410/31 EX
Engine	Tata 497 SP Turbo Charged Inter-cooled Diesel	Tata 497 SP Turbo Charged Inter-cooled Diesel
Engine Power	75 KW @ 2800 rpm (100 HP)	75 KW @ 2800 rpm (100 HP)
Engine Torque	300 Nm @ 1400 - 1500 rpm	300 Nm @ 1400 - 1500 rpm
Driveline	Dry Single Plate, 280 mm dia Clutch	Dry Single Plate, 280 mm dia Clutch
Gearbox	G 380 5 Forward + 1 Reverse	G 380 5 Forward + 1 Reverse
Brakes	Hydraulic (Front and Rear) with EEB Fitment	Hydraulic (Front and Rear) with EEB Fitment
Suspension	Leaf Spring, Hydraulic - Double Acting Telescopic and Anti-roll Bars on Front and Rear	Leaf Spring, Hydraulic - Double Acting Telescopic and Anti-roll Bars on Front and Rear
Steering	Variable Ratio Steering	Variable Ratio Steering
Battery	12 Volts 75 Ah	12 Volts 75 Ah
Alternator (Max o/p)	65 Amps	65 Amps
Tyres	4 +1 Tyres 7.50 x 16 - 16 PR	4 +1 Tyres 7.50 x 16 - 16 PR
Fuel Tank	60 Ltrs	60 Ltrs
Turning Circle Diameter	11 m	11 m
Maximum GVW	4800 Kgs	4800 Kgs
	Body	
Seating Capacity & Layout	16+1, 2x2	20+1, 2x2
Structure Structure	Pre-treated structure for corrosion resistance, long life body	Pre-treated structure for corrosion resistance, long life body
Floor	Anti-skid Vinyl Flooring	Anti-skid Vinyl Flooring
Passenger Door	Jack Knife type	Jack Knife type
Front Windshield	Single	Single
Rear Windshield	Single piece tempered glass	Single piece tempered glass
Emergency Exits	Rear of bus, breakable rear glass with hammer & Side Emergency Door on the rear RHS of the bus	Rear of bus, breakable rear glass with hammer & Side Emergency Door on the rear RHS of the bus
Side Windows	Side - sliding glasses	Side - sliding glasses
Driver's Partition	Half - Glass	Full partition with M S Pipe, glass at top half
First-aid Box	One no. behind driver	One no. behind driver
Tool Box	Provided	Provided
Roof Lamps	2 Red Rear and 2 White Front	2 Red Rear and 2 White Front
Step Lamp	No	No
Fire Extinguisher	1 no. of 1 kg capacity	1 no. of 1 kg capacity
Hat-rack	No. of Fig capacity	Padded
Window Guardrail	Four Row	Four Row
Bell Switch	1 no. on Stanchion Pipe	1 no. on Stanchion Pipe
Emergency Alarm	Door Open Alarm	Door Open Alarm
Colour Scheme	Fluorescent Yellow Exterior Colour	Fluorescent Yellow Exterior Colour
Fire Retardant Material	Fire retardant material for all the interior material used in the bus	Fire retardant material for all the interior material used in the bus
Side Luggage Boot	No No	No No
Air-conditioner	No	No
		limensions
Length (mm)	5125	5605
Height (mm)	2615	2615
Width (mm)	2150	2150
Wheel Base (mm)	2750	3100