

SPECIFICATIONS

TATA LPK 407



IDEAL TO TRANSPORT Hardware items, Raw materials, Sand. Metal



ENGINE

Model TATA 497 SP Turbo (Euro II)

Water-cooled direct injection Diesel Engine

No. of cylinders 4 Cylinders in line Capacity 2956 CC Max. Engine Output 75 PS @ 2800 rpm

Max. Torque 225 Nm @ 1250-1800 rpm

CLUTCH Single plate dry friction type, 280 mm dia

GEAR BOX GBS-27 Synchromesh, 5F, 1R

Grar Ratios 1st - 7.36, 2nd - 4.38, 3rd - 2.48, 4th - 1.58, 5th - 1.00, Rev. - 6.67

7.50 x 16 - 16 PR Type (Front & Rear)

Front-2 Rear-4 Spare-1

FUEL TANK 60 Litres

WHEELS & TYRES

Max. climbing ability in 1st gear:26%Minimum turning circle radius (mts)5.1Wheel base (mm)2775Weight (kg)2535Max. permissible FAW3715Max. permissible GVW6250

FRAME Ladder-type framewith riveted/bolted cross members. DxWxT (mm): 200x60x5

SUSPENSION Semi-elliptical leaf spring at front at front and rear with auxiliary spring

at rear only

SHOCK ABSORBER Hydraulic double acting telescopic

type at front & rear

SALIENT FEATURES

- LCV Tipper equipped with Power Steering
- Better manoeuvrability in narrow lanes-lowest turning circle radius of 5.1 mtrs
- Can make way through steeper gradients higher gradeability of 26%
- Strong & durable chassis, exclusively designed for tipping application
- Larger clutch (280 mm dia) for easy gear shifing
- Deluxe Ex cabin
- Suitable for all kinds of terrain

THE TATA ADVANTAGE



Powerful Turbo Engine

Powerful turbocharged engine provides superior pick up and ensures peak performance and fuel economy in all kinds of application. A higher starting torque and a flatter torque curve provides more pulling power and enhances performance in both city and ling distance traveling.



Reliable And Durable Performance

From roughest road to toughest job TATA vehicles are built to give years of dependable service even in extreme road and weather conditions. The cabs and frames are designed to be highly rigid and are extensively treated to prevent corrosion.



Enhanced Safety

A superior Tilt cab construction ensure driver safety in all terrains. Wide side mirrors, larger headlamps and larger windscreen provide greater visibility at all hours.



Easy Maintainability

Tilt cabin provide easy accessibility to regular maintenance items. The fuse and relay boxes and brakefluid reservoir are conveniently located and simple engine maintenance can be performed through the front bonnet of the cabin.



Smooth And Comfortable Operation

Turbocharger act as an additional silencer as it is placed on the exhaust side, thereby, reducing engine noise considerably. Easy drive power assisted steering enables maneuverability within the city. Enhanced ventilation and ergonomic seats make the drive comfortable and easy driver fatique.

CAUTION: Do not weld or drill on chassis frame

Accessories shown in the picture or elsewhere do not constitute standard fitment. The specifications are subject to change without notice. These are indicative specifications for reference only.

WARRANTY: 18 Months / 150,000 km

(Which ever comes first)

To know the price of this truck, then please visit TAB - India