SPECIFICATIONS



| | Starbus Skool 26 | |
|---------------------------|--|---|
| Emission | Bharat Stage III | Bharat Stage IV |
| Chassis Platform | Tata LP 410 TT/34 BS III | Tata LP 410 TT/34 BS IV |
| Engine | Tata 497 SP Turbo Charged Inter-cooled Diesel | Tata 497 Turbo Charged Inter-cooled Common Rail Direct Injection Engine Diesel |
| Engine Power | 75 KW @ 2800 rpm (100 HP) | 75 KW @ 2600 rpm (100 HP) |
| Engine Torque | 300 Nm @ 1400 - 1500 rpm | 300 Nm @ 1300 - 1800 rpm |
| Driveline | Dry Single Plate, 280mm dia Clutch | Dry Single Plate, 280mm dia Clutch |
| Gearbox | GBS 27, 5 Forward + 1 Reverse | GBS 550, 6 Forward + 1 Reverse |
| Brakes | Vacuum Assisted Dual Circuit Hydraulic Brake with EEB Fitment | Vacuum Assisted Dual Circuit Hydraulic Brake with EEB Fitment |
| Suspension | Leaf Spring, Hydraulic - Double Acting Telescopic and Anti-roll Bars on Front and Rear | Leaf Spring, Hydraulic - Double Acting Telescopic and Anti-roll Bars on Front and Rear |
| Steering | Variable Ratio Steering | Variable Ratio Steering |
| Battery | 12 Volts 75 Ah | 12 Volts 120 Ah |
| Alternator (Max o/p) | 65 Amps | 65 Amps |
| Tyres | 6+1 Tyres 7.50x16 - 16 PR | 6+1 Tyres 7.50x16 - 16 PR |
| Fuel Tank | 60 Ltrs | 60 Ltrs |
| Turning Circle Diameter | 12.3 m | 12.3 m |
| Maximum GVW | 6520 Kgs | 6520 Kgs |
| | Body | |
| Seating Capacity & Layout | 26 +1, 2x2 | |
| Structure | Galvanized Tubular Structure | |
| Floor | 12mm Plywood (Fire Retardant) with Anti-skid Vinyl | |
| Passenger Door | 1 no. Jack Knife Door | |
| Front Windshield | Single laminated glass 6.76 mm thick | |
| Rear Windshield | Single piece tempered glass | |
| Emergency Exits | Rear of bus, breakable rear glass with hammer & Side Emergency Door on the rear RHS of the bus | |
| Side Windows | Side - sliding glasses | |
| Driver's Partition | Full partition with M S Pipe, glass at top half | |
| First-aid Box | One no. behind driver | |
| Tool Box | Provided | |
| Roof Lamps | 2 Red Rear and 2 White Front | |
| Step Lamp | Yes | |
| Fire Extinguisher | 1 no. of 2 kg capacity | |
| Hat-Rack | Tubular Padded | |
| Window Guardrail | Four Row | |
| Bell Switch | 1 no. on Stanchion Pipe | |
| Emergency Alarm | Door Open Alarm | |
| Colour Scheme | Fluorescent Yellow Exterior Colour | |
| Fire Retardant Material | Fire retardant material for all the interior material used in bus | |
| Side Luggage Boot | Yes | |
| Air-conditioner | No | |
| | Overall Dimensions | |
| Length (mm) | 6870 | |
| Height (mm) | 2865 | |
| Width (mm) | 2200 | |
| Wheel Base (mm) | 3400 | |
| Internal Height (mm) | 1900 | |