

SPECIFICATION OF SUPER-12 TC TRUCK



Variants		
DIMENSIONS		
Wheelbase (mm)		3940
Overall Length (mm)		7220
Overall Width(mm)		2400
Overall Height (mm)		2480
Track Front(mm)		2022
Track Rear(mm)		1676
Min Ground Clearance		300
GVW(kgs)		11990
CARGO BODY		
Inside Length (mm)		5240
Inside Width (mm)		2400
Load Area(mm)		5240X2400
Empty Vehicle Weight(Kg)		4300
TYRE		
Tyres (Front & Rear)		8.25 X 20 -14 PR
No of Tyres		6+1
ENGINE SPECIFICATION		
Engine Type		SLT3 & Numeral
Displacement		3455 cc
Max Power		75 KW @ 3000 rpm- BS-III
Max Torque		270Nm@1750~2000 RPM- BS-III
Clutch		Single plate Diaphragm Type - Dia. 260mm
TRANSMISSION		
Gear		Manual 5F and 1R
CHASSIS FRAME		
Member size		C- Type Chassis Frame
SUSPENSION		
Front & Rear Suspension		Semi-Elliptical Type Multi Leaf Spring (Front & Rear) Shock Absorber: Hydraulic Dampers
ELECTRICAL		

Battery	12V-70 Ah
Alternator	35 Amp
STEERING	Manual type, recirculating ball / Power Steering (Optional)
BRAKES	
Service Brakes	Dual Circuit Full Air Brakes
Fuel tank	180 lts
FEATURES	
	<p>*Powerful Engine-Higher Pickup, Higher Torque at lower RPM, Gradeability and Fuel Efficiency .</p> <p>* Heavy Duty Gear Box and Bigger Clutch- Longer Life.</p> <p>, Provide better Strength and Rigidity .</p> <p>* Steering with variable Gear Ratio-Less Driver Fatigue .</p> <p>* Roof Ventilation,less Driver Fatigue and Better Comfort.</p> <p>* Ready availabilty of Spares at reasonable Price .</p>